

Retail

Food
Service

Financial

Bank

Telecom

Your Reliable Provider

3inch Thermal barcode Printer (LabelPrint 300)

Features:

- * 152mm~200mm/s high-speed printing
- * Compatible with ESC/POS and TSPL instructions.
- * Support vector font
- * Movable sensor, automatic detection of paper
- * A variety of interfaces are optional
- * 1.5 inch display screen
- * Visual window design
- * Big gear, longer service life.



Specification:

Printer Specifications	Print Method	Direct thermal line
	Resolution	203 dpi
	Print Width	80mm
	Print Speed	152~200mm/s
	Interface	USB (Standard)
		USB + Bluetooth (Optional)
		USB + WiFi (Optional)
		USB + Serial + Ethernet (Optional)
	Print head temperature detect	Thermal sensitive resistance
	Print Head Position detect	Mircoswitch
Media	Paper Type	Thermal paper, Thermal label, Adhesive thermal paper, sticker, Medical wristband ect
	Media Width	15-85mm
	Media Roll Core Size	25.4mm
	Media Diameter	100mm (Max.)
	Paper Off Type	Front paper out, Tear off
BarCode and Fonts	Enlargement & Rotation	Vector font, 0°、90°、270°、360° rotation
	Character Size	Font 0 ~ Font 8, TST24, TSS24
	Barcode	CODE128, EAN128, ITF, CODE39, CODE93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPCA+2, UPCA+5, UPCE+2, UPC-E+5, CPOST, MSI, MSIC, PLESSEY, ITF14, EAN16, QRCODE
	Graphics Processing	Support PCX/BMP files to be downloaded FLASH/DRAM
Operating Characteristics	Power Supply	24V/2.5A
	Work Environment	Temperature: 5 ~ 45℃, Humidity: 20 ~ 90%
	Storage Environment	Temperature: -20 ~ 55℃, Humidity: 20 ~ 93%
Physical Characteristics	Weight	1.62kg
	Dimension	205.5*146*143mm
Others	Reliability	50KM



Barcode



Paper sensor



Easy load



Compact design



High speed



Various interface



Paper width